



PILA Batten

PILA BN007C LED40S/840 L1200

PILA Batten – LED Module, system flux 4000 lm –
840 neutral white – Length 1200 mm

Benefits

- Applicable for wide range of applications
- Supports energy saving
- Reliable quality



CRI



20,000 h



220-240 Vac



Safety Class



IP20

Product data

General information

Lamp family code	LED40S [LED Module, system flux 4000 lm]
Light source color	840 neutral white
Light source replaceable	-
Number of gear units	1 unit
Driver/power unit/transformer	PSU [Power supply unit]
Driver included	Yes
Emergency Lighting	-
Optic type	-
Control interface	No
Connection	Fly wire 0.15 m
Protection class IEC	Safety class II
Mounting	-
CE mark	Yes
EU RoHS compliant	Yes
Constant light output	No
Number of products on MCB of 16 A type B	-
Service tag	-
Product family code	BN007C [PILA Batten]

Operating and Electrical

Input Voltage	220-240 V
Input Frequency	50 to 60 Hz
Inrush current	-
Inrush time	-
Power Factor (Min)	> 0.9



Surge Protection (KV)	-
-----------------------	---

Controls and Dimming

Dimmable	No
----------	----

Mechanical and Housing

Housing Material	Polycarbonate
Optical cover/lens material	-
Optical cover/lens finish	-
Overall length	1187 mm
Overall width	54 mm
Overall height	36 mm
Color	White
Accessory	-

Approval and Application

Ingress protection code	IP20
Mech. impact protection code	-

Initial Performance (IEC Compliant)

Initial luminous flux (system flux)	4000 lm
Init. Corr. Color Temperature	4000 K
Init. Color Rendering Index	> 80
Initial chromaticity	-
Initial input power	30 W

Over Time Performance (IEC Compliant)

Lifetime L70B50	20,000 h
-----------------	----------

Application Conditions

Performance ambient temperature Tq	-
------------------------------------	---

Product Data

Full product code	-
Order product name	PILA BN007C LED40S/840 L1200
EAN/UPC - Product	8720169761056
Order code	911401829687
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	911401829687
Net Weight (Piece)	0.255 kg

Dimensional drawing

